



atn501 White

- Printable 1 side (outside)
- Cost efficient
- Coated both sides

ATN501 provides highly accurate printing at a competitive price level compared to other printable fabric materials. The coating is formulated to make this material printable with Thermal Transfer technology on the outside.


Selected for optimal compatibility with **AXR®TX** Thermal Transfer Ribbon.

Resistances

- | | |
|------------------------------|---------------------|
| Washing
AATCC61-2A | Ironing |
| Stone washing | Tanning |
| Enzyme washing | Dry cleaning |
| Dyeing process | Anti-fray |

Fabric specifications

- Color:** white
- Density:**
 - Warp: 46 yarns/cm
 - Weft: 21 yarns/cm
- Total weight: 65 g/m²**
 - Coating weight 34 g/m²
 - Fabric weight 31 g/m²
- Thickness:** < 0,130mm



NYLON taffeta

POLYESTER

> **atp811** white
Dyeing process resistant

> **atp812** white
Dyeing process resistant

SATIN

> **ats821** white
Anti-fray

> **ats811** white
Dyeing/Tanning/Stonewashing...

> **ats601** white

> **ats612** white
Recycled yarns

> **ats602** white

NYLON

> **atn501** white

> **atn802** white
Roll up resistant

> **atn602** white

Printable 1 side only

Printable both sides

Roll specifications

- Core diameter:** 1", 1,5", 2", 3"
 - Roll width:** min 20 mm, max 220 mm
 - Roll length:** min 50 m, max 400 m
- Refer to the offer brochure for more information

Certifications

- REACH / SVHC** 1907/2006/EC

Storage conditions

- Recommended:** 12 months
- Humidity rate:** 20-80%
- Temperature:** 5-35°C (40-95°F)