



## aTP811 White

- Printable 1 side (outside)
- Smooth touch & tear resistant
- Dyeing process resistant
- Coated one side

**Polyester Taffeta** is a polyester fiber based fabric. This material gives excellent resistance to harsh mechanical manipulation (tearing, scratching...), a smooth and supple surface which brings comfort in case of skin contact. The coating allows it to be printable with Thermal Transfer technology and resist to the dyeing process and stone washing.

Selected for optimal compatibility with **AXR®TX** Thermal Transfer Ribbon.

## 100% POLYESTER taffeta

### POLYESTER

> **aTP811** white  
Dyeing process resistant

> **aTP812** white  
Dyeing process resistant

### SATIN

> **aTS821** white  
Anti-fray

> **aTS811** white  
Dyeing/Tanning/Stonewashing...

> **aTS612** white  
Recycled yarns

> **aTS602** white

> **aTS601** white

### NYLON

> **aTN501** white

> **aTN802** white  
Roll up resistant

> **aTN602** white

Printable 1 side only

Printable both sides

### Resistances

**Washing**  
Domestic 80-85°C

**Ironing**

**Stone washing**

**Tanning**

**Enzyme washing**

**Dry cleaning**

**Dyeing process**

**Anti-fray**

### Roll specifications

- **Core diameter:** 1", 1,5", 2", 3"
- **Roll width:** min 20 mm, max 220 mm
- **Roll length:** min 50 m, max 400 m


Refer to the offer brochure for more information

### Certifications

- **REACH / SVHC** 1907/2006/EC



### Fabric specifications



- **Color:** white
- **Density:**
  - Warp: 42 yarns/cm
  - Weft: 31 yarns/cm
- **Total weight: 92 g/m<sup>2</sup>**
  - Coating weight 30 g/m<sup>2</sup>
  - Fabric weight 62 g/m<sup>2</sup>
- **Thickness:** < 0,165mm

### Storage conditions

- **Recommended:** 12 months
- **Humidity rate:** 20-80%
- **Temperature:** 5-35°C (40-95°F)