



## ATS602 White

- Printable both sides
- Cost efficient
- Uncoated

**Satin Polyester** is a polyester fiber based fabric. The polyester fibers give the material an excellent resistance to tearing and the satin weaving allows it to have a soft and comfortable look and feel.

The calendering of **ATS602** allows it to be printed on both sides.

Selected for optimal compatibility with **AXR<sup>®</sup>TX** Thermal Transfer Ribbon.

### Resistances

- |                              |                     |
|------------------------------|---------------------|
| <b>Washing</b><br>AATCC61-2A | <b>Ironing</b>      |
| Stone washing                | Tanning             |
| Enzyme washing               | <b>Dry cleaning</b> |
| Dyeing process               | Anti-fray           |

### Fabric specifications



- Color:** white
- Density:**
  - Warp: 142 yarns/cm
  - Weft: 40 yarns/cm
- Total weight: 117 g/m<sup>2</sup>**
  - Fabric weight 117 g/m<sup>2</sup>
  - This fabric is uncoated
- Thickness:** < 0,115mm

## 100% SATIN POLYESTER

POLYESTER	
> <b>ATP811</b> white Dyeing process resistant	> <b>ATP812</b> white Dyeing process resistant
SATIN	
> <b>ATS821</b> white Anti-fray	> <b>ATS612</b> white Recycled yarns  > <b>ATS602</b> white
> <b>ATS811</b> white Dyeing/Tanning/Stonewashing...	
> <b>ATS601</b> white	
NYLON	
> <b>ATN501</b> white	> <b>ATN802</b> white Roll up resistant  > <b>ATN602</b> white

**Printable 1 side only**      **Printable both sides**

### Roll specifications

- Core diameter:** 1", 1,5", 2", 3"
  - Roll width:** min 20 mm, max 220 mm
  - Roll length:** min 50 m, max 400 m
- Refer to the offer brochure for more information*

### Certifications

- REACH / SVHC 1907/2006/EC**



### Storage conditions

- Recommended:** 12 months
- Humidity rate:** 20-80%
- Temperature:** 5-35°C (40-95°F)