



## ats821 White

- Printable 1 side (outside)
- Anti-fray
- Coated one side

**Satin Polyester** is a polyester fiber based fabric. The polyester fibers give the material an excellent resistance to tearing and the satin weaving allows it to have a soft and comfortable look and feel. The coating of **ATS821** allows it to resist to fraying.

Selected for optimal compatibility with **AXR®TX** Thermal Transfer Ribbon.

### Resistances

- |                       |              |
|-----------------------|--------------|
| Washing<br>AATCC61-2A | Ironing      |
| Stone washing         | Tanning      |
| Enzyme washing        | Dry cleaning |
| Dyeing process        | Anti-fray    |

### Fabric specifications



- Color:** white
- Density:**
  - Warp: 120 yarns/cm
  - Weft: 41 yarns/cm
- Total weight: 109 g/m<sup>2</sup>**
  - Coating weight 4 g/m<sup>2</sup>
  - Fabric weight 105 g/m<sup>2</sup>
- Thickness:** < 0,125mm

## 100% SATIN POLYESTER

- POLYESTER**
- > **atp811** white  
Dyeing process resistant
  - > **atp812** white  
Dyeing process resistant

- SATIN**
- > **ats821** white  
Anti-fray
  - > **ats811** white  
Dyeing/Tanning/Stonewashing...
  - > **ats601** white
  - > **ats612** white  
Recycled yarns
  - > **ats602** white

- NYLON**
- > **atn802** white  
Roll up resistant
  - > **atn602** white
  - > **atn501** white

**Printable 1 side only**      **Printable both sides**

### Roll specifications

- Core diameter:** 1", 1,5", 2", 3"
  - Roll width:** min 20 mm, max 220 mm
  - Roll length:** min 50 m, max 400 m
- Refer to the offer brochure for more information*

### Certifications

- REACH / SVHC** 1907/2006/EC



### Storage conditions

- Recommended:** 12 months
- Humidity rate:** 20-80%
- Temperature:** 5-35°C (40-95°F)